


May | 2023

AU

Reid™ Panel Shims

Compliance Document



Reid™ Panel Shims
comply with
AS3850.1:2015
(+AI 2019)

reid.com.au | 1300 780 250

Reid™ Panel Shims



Reid™ Panel Shims have been independently tested & rated with a 20t Working Load Limit (WLL) as determined in accordance with AS3850.1:2015 (+A1 2019).


Figure 1: Blue Full Panel Shim (2mm)



Figure 2: Reid™ Panel Shim Range



Full Shim



Reid™ Panel Shims comply with AS3850.1:2015 (+A1 2019)


















Reid™ Panel Shims Key Features:

- Reid Panel Shims have been designed for the temporary leveling & support of precast elements.
- They are manufactured in our ISO accredited Australian factory.
- Reid Panel Shims are colour coded by thickness, for easy identification.
- They are also permanently marked with the Reid logo & 20t WLL for easy identification.
- Reid Panel Shims have a minimum coefficient of friction of 0.3.



Compliance Details

Table I: AS3850.1:2015 (+A1 2019) Compliance Details

| Clause | Requirement | Compliant |
|--------|---|--|
| 2.2 | The Working Load Limit has been determined by testing in accordance with Appendix A, using a FOS per Table 2.1 |  |
| 2.8.1 | Deform elastically at full load Not continue to creep more than 5% up to 15 mins at full load; Not continue to creep more than 3% after 15 mins at full load up to 48 hrs; Resist corrosion stains, not be affected by cold weather, alkali, ground chemicals Not oxidize or expand when exposed to moisture Permanently marked with WLL & for traceability WLL derived using statistical methods based on ultimate load determined from the onset of plastic deformation |        |
| 2.8.2 | The Working Load Limit has been determined by testing in accordance with Clause 2.2 & the compressive strength of the material per Appendix A. |  |
| A3 | Testing and recording of results |  |
| A4 | A4 Statistical evaluation of test results, using formula A4, $X_k = x(1 - k_s \text{COV})$. 4 |  |
| A5 | Production Validation through testing to confirm compliance of critical specification requirements (dimensions, material properties and load bearing capacity where appropriate). |  *see note on p5 |
| A11.3 | Shim specimen to be conditioned in accordance with ASTM D618, procedure A. |  |
| A11.4 | Compression test per ASTM D695 |  |
| A11.5 | The compressive strength shall be expressed in MPa and Determined from the stress to deform or rupture the specimen. |  |
| A11.6 | Tested with WLL load X FoS per table 2.1 for 48 hrs @ 15-25° C. Tested with WLL load for 12 hrs @ 40° C. |   |




Product Specifications

Table 2: Full Panel Shim Product Codes

| Product Codes | Shim Thickness (mm) | Dimensions (mm) | Working Load Limit (WLL) | Colour | Pack Qty |
|---------------|---------------------|-----------------|--------------------------|--------|----------|
| SHIM01 | 1 | 150 x 100 | 20t | Brown | 100 |
| SHIM02 | 2 | 150 x 100 | 20t | Blue | 200 |
| SHIM03 | 3 | 150 x 100 | 20t | Green | 100 |
| SHIM05 | 5 | 150 x 100 | 20t | Yellow | 100 |
| SHIM10 | 10 | 150 x 100 | 20t | Black | 40 |
| SHIM15 | 15 | 150 x 100 | 20t | Grey | 40 |
| SHIM20 | 20 | 150 x 100 | 20t | White | 30 |


Reid™ Full Panel Shim Features & Markings



Testing & Verification



Reid™ Panel Shim packaging contains our reid logo, WLL & batch number for traceability



In addition to batch testing, our Panel Shims have also been independently tested by an accredited NATA laboratory.



NATA Independent Testing Scenarios



Figure 3: Compression Test



Figure 4: Test setup used for elevated temperature compression test

Terms and Conditions

Important Disclaimer: Any engineering information or advice (“Information”) provided by Reid™ in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, Reid will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information.

All Reid™ branded products and all products manufactured at our Melbourne manufacturing facility are designed, manufactured, tested and supplied in compliance with our Quality Management System which has been independently audited and certified by SAI Global to ISO 9001:2015. Reid™ undertake strict quality control processes to ensure performance specifications and metallurgical properties are maintained.

To reflect the progress of the industry and the new innovative uses of precast and tilt-up construction, Australian Standard AS 3850 was updated in 2015 and amended in 2019.. This update included a change in title to AS 3850:2015 Prefabricated Concrete Elements, a widened scope to include all prefabricated elements in Building Construction and splitting of the document into two parts:

- Part 1, called ‘General requirements’ details the new performance and testing requirements for suppliers of componentry into the industry. These new requirements are significantly different to AS 3850:2003 and should enable the industry to have greater confidence in the products that they are specifying and using;
- Part 2, called ‘Building construction’, aligns with the 2008 National Code of Practice for Precast, Tilt-Up and Concrete Elements in Building Construction and focuses on the interrelation of the various stages of manufacture, construction, transport and erection. It is specifically for the construction design and documentation of prefabricated concrete elements in building construction and provides guidance for the Erection Designer and highlights the importance of the Erection Design and Documentation.

The new AS 3850.1:2015 (Incorporating Amendment 1 - 2019) is central for the safe, efficient and cost-effective manufacture, construction, transport and erection of prefabricated concrete elements.

customer service

Reid™ Australia

Customer Service Centre

Tel: 1300 780 250

Email: sales@itwcsanz.com

Web: reid.com.au

Reid™ Construction Systems (RCS) 1 Ramset Drive, Chirnside Park 3116

Information in this document is correct at the time of printing. Readers should contact RCS or consult RCS detailed technical information to ensure product is suitable for intended use prior to purchase. ITW Australia Pty Ltd ABN 63 004 235 063 trading as RCS

© Copyright May 2023™ Trademarks of Cetram Pty. Ltd. Used under license by RCS

Important Disclaimer: Any engineering information or advice ("Information") provided by RCS in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, RCS will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information.

